

Specification Sheet for Max2000 (41.25")

Axle Length	41.25"
Brace Height	7.5"
Limb Length	17"

*Note:- Brace heights may vary depending on cam size and type. It is more important to use the axle length as a point of reference, more than the brace height.

STRING AND CABLE CHARTS

	String	Power Cable	Control Cable	Split Cable (Long)	Split Cable (Short)
<i>Rapid Cam No.1</i>	59	42.5	-	67	9.5
<i>Rapid Cam No.2</i>	55.75	42.5	-	67	9.5
<i>Rapid Cam No.3</i>	51.75	42.5	-	67	9.5
<i>T-Wheel No.1</i>	60.25	42.5	-	67	9.5
<i>T-Wheel No.2</i>	57	42.5	-	67	9.5
<i>T-Wheel No.3</i>	55	42.5	-	67	9.5
<i>T-Wheel No.4</i>	51.5	43	-	67	10

MODULE SELECTION CHARTS

RAPID CAM	A	B	C	D	E
<i>Cam No.1</i>	29	30	31	32	33
	F1	F	G	H	
<i>Cam No.R3</i>	26	27	28	29	
<i>Cam No.R4</i>	23	24	25	26	

T-WHEEL	HS1 65% SS1 65%	HS1 55% SS1 55%	HS2 65% SS2 65%	HS2 55% SS2 55%
<i>Cam No.1</i>	30		29	
<i>Cam No.2</i>	28		27	
<i>Cam No.3</i>	27		26	
<i>Cam No.4</i>	25		24	